

INSTALLATION INSTRUCTIONS



HALF DOOR SIDE MIRRORS 1987-2006 WRANGLER YJ/TJ/LJ SB7694

COMPONENTS



Part	QTY
Mirror Assembly	2
Gasket	2
M6-1.0x15mm Countersunk Screw	6

INFORMATION

GENERAL

Carefully read through this entire instruction manual thoroughly before attempting to install this part. Photos may vary from your vehicle. Installation will remain the same.

Jeep®, Wrangler®, YJ®, TJ® and LJ® are registered trademarks of Stellantis N.V.

ADJUSTMENT



WARRANTY



INSTALL



Start by removing any factory mirrors and hardware from your YJ, TJ, or LJ.

On the driver's side, position the **Half Door Mirror** with the **Gasket** placed between the mirror and the hinge on your Jeep. Align the mounting holes and fasten the mirror using the supplied M6 countersunk screws. After confirming proper alignment and fitment, tighten the screws to 5 ft-lbs of torque. Repeat the same installation steps on the passenger side. **Installation is now complete.**

For 1987 YJ owners: Drilling may be required for proper fitment.



For Tech Support / Warranty Information please call 1-888-717-5797, email info@smittybilt.com
Smittybilt, 1017 W 600 N, Suite 4, Ogden, UT 84404