Installation Instructions



2020+ Ford Bronco® 4 Door Angular Drop Steps S/BEXF214B-TX





Introduction

Thank you for choosing Smittybilt accessories for your Ford Bronco®. If you would like to view our full range of available accessories, please visit us at www.smittybilt.com







Ford Bronco® Cab Cover

Fridges

Recovery Gear and Winches

Ford® and Bronco® are registered trademarks of Ford Motor Company®

Important Notes Before Starting



IMPORTANT NOTE

Carefully read through this entire instruction manual thoroughly before attempting to install this part. Image are for illustration purposes and may vary from your vehicle. Installation will remain the same.



WARNING

Serious injury can occur when working on vehicles alone.

When possible, work with another person to reduce risk of injury from strain or other dangers that can occur when working alone.



WARNING


The weight limit for these steps is 445lbs. Do not exceed this weight limit.

Exceeding this weight limit can cause damage or personal injury.



Box Contents & Product Safety

F2172B-TX Box Contents



ID	Part Description	QTY
1	Driver Side Nerf Step	1
2	Passenger Side Nerf Step	1
3	M10-1.5x30mm Hex Head Bolt	12
4	M10 Flat Washer	12
5	M10 Split Lock Washer	12

Installation Instructions: Ford Bronco® Nerf Steps



Step 1:

If your Bronco® currently has running boards, remove them prior to proceeding.
Remove steps and hardware from the box.
Confirm you have all the components needed for installation. Then, remove the **Driver Side Nerf Step** from the packaging and measure the distance between the first set of mounting brackets.



Installation Instructions: Ford Bronco® Nerf Steps



Step 2:

Underneath your Bronco®, clean the mounting surfaces using some rubbing alcohol and a cloth. Find the first set of mounting holes and confirm the distance is the same as measured in **Step 1**.



Step 3:

With the assistance of a second person, lift the step up into place and align the (4) welded mounting brackets to the pre-threaded holes in the frame of your truck. Loosely secure the brackets to the vehicle using (6) M10-1.5x30mm Hex Bolts, (6) M10 Flat Washers, and (6) M10 Split Lock Washers. Do not torque the hardware yet.




Step 4:

Confirm you are happy with the fitment and placement of the step. Then torque all (6) M10 Bolts to spec using the guide on Page 6.



Installation Instructions: Ford Bronco® Nerf Steps



Step 4:

Repeat Steps 1-4 for the Passenger Side Nerf Step.



Step 5:


Installation is now complete.




Bolt Torque Specifications

Use this only as a guide for hardware without a called out torque specification in the instruction manual.

Bolt Torque and ID								
Decimal System			Metric System					
All Torques in Ft. Lbs. Maximums								
Bolt Size	Grade 5	Grade 8	Bolt Size	Class 9.8	Class 10.9	Class 12.9		
5/16	15	20	M6	5	9	12		
3/8	30	45	M8	18	23	27		
7/16	45	60	M10	32	45	50		
1/2	65	90	M12	55	75	90		
9/16	95	130	M14	85	120	145		
5/8	135	175	M16	130	165	210		
3/4	185	280	M18	170	240	290		





M12-1.25x50 HHCS

T
L
X

G= Grade (Bolt Strength)

D= Nominal Diameter (Inches)

T= Thread Count (Threads per Inch)

L= Length (Inches)

X= Description (Hex Head Cap Screw)

P= Property Class (Bolt Strength)

D= Nominal Diameter (Millimeters)

T= Thread Pitch (Thread Width, mm)

L= Length (Millimeters)

X= Description (Hex Head Cap Screw)



Notes and Disclaimers

Product cleaning and maintenance instructions

Stainless Steel Finish – Aluminum polish may be used to polish small scratches and scuffs on the finish. Mild soap, window or glass cleaner may be used to clean the finish. Dual state powder coat finish – Mild soap, window or glass cleaner may be used to clean the finish. In order to protect the finish, you may wax your product on a regular basis with pure carnauba automotive wax. Do not use any types of soap, polish or was that contains abrasive that could damage the finish. Textured coated finishes should be cleaned with a mild soap on a damp sponge. Do not apply polish or wax that requires to be removed by means of buffing. This type of wax is commonly used at car wash facilities. Chrome Finish – Mild soap, window or glass cleaner may be used to clean the finish. In order to protect the finish, you should wax your product on a regular basis with pure carnauba automotive wax. Do not use any types of soap, polish or was that contains abrasive that could damage the finish.

SMITTYBILT ADVANTAGE WARRANTY

LIMITED-LIFETIME WARRANTY FOR STRUCTURAL COMPONENTS

5-YEAR FINISH WARRANTY

Smittybilt Automotive Products, LLC (SAP) warrants to the original purchaser that (a) the physical components (e.g., metal components, welds, etc.) of any SAP **Ford Bronco® 4 Door Angular Drop Steps** will be free of defects in material and workmanship for the lifetime of the product from the date of purchase of the Nerf Steps, and (b) the finish will be free of defects in material and workmanship for a period of 5-years from the original date of purchase. This warranty applies only to the original purchaser of the Nerf Steps and is non-transferable. To obtain any warranty service, you must provide SAP with a proof of purchase and date of purchase that is acceptable to SAP, such as a copy of your purchase receipt.

This warranty does not cover labor of part replacement of the Nerf Steps. SAP will, at its sole discretion, provide replacement part(s) for a defective Nerf Step or component, provided this is done within the warranty period. To request assistance under warranty, one must call or email using the phone number or email at the bottom of this page. This warranty does not apply (1) wearable components; or (2) if the Nerf Step(s) has/have been damaged, including, but not limited to: abuse, misuse, collision, modification, misapplication, improper installation, or improper service. This warranty is void if any SAP serial number has been removed or defaced; or if the Nerf Steps are used for any commercial, industrial, or rental applications. This warranty only applies to Nerf Steps bought, sold, and used within the Untied States or Canada unless otherwise specifically agreed in writing by SAP.

THE WARRANTY SET FOURTH ABOVE IS THE ONLY WARRANTY. THERE ARE NO OTHER WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO IMPLIED WARRANTIES OF MERCHANT ABILITY OR FITNESS FOR A PARTICULAR PURPOSE. ANY IMPLIED WARRANTY WHICH BY LAW MAY NOT BE EXCLUDED IS LIMITED TO A DURATION OF ONE (1) YEAR FROM THE DATE OF ORIGINAL RETAIL PURCHASE OF THE PRODUCT. No SAP dealer, agent, or employee is authorized to make any modification, extension or addition to this warranty. SAP SHALL NOT BE LIABLE FOR SPECIAL, INDIRECT, INCIDENTAL OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, LOST PROFITS, DOWN TIME OR LOSS OF USE) UNDER ANY LEGAL THEORY, EVEN IF SAP WAS ADVISED OF THE POSSIBILITY OF SUCH DAMAGES. Some states do not allow the exclusion of implied warranties or the exclusion or limitation of liability for incidental or consequential damages, or limitations on how long an implied warranty lasts, so the above limitation or exclusion may not apply to you. This Warranty gives you specific legal rights. You may also have other rights that vary from state to state. SAP reserves the right to change product design without notice. In situations in which SAP has changed a product design, SAP shall have no obligation to upgrade or otherwise modify previously manufactured products. For warranty inquires contact SAP at:

Smittybilt Automotive Products, LLC

Customer Service Department

Call 1-800-776-0767 or Email info@smittybilt.com



WARNING: Cancer and Reproductive Harm www.P65Warnings.ca.gov

